

| Product Code | Description | Weight | Air Permeability | Air Permeability | Initial Pressure Drop | Filtration Class | Roll Length |
|--------------|-------------|--------|------------------|----------------------------|-----------------------|---|-------------|
| | | gr/m2 | Cfm @125pa | l/m ² .s @200pa | pa | EN779:2012 / EN1822 / ISO 16890 / EN149 / NIOSH 42 CFR 84 / EN14683 | mt |

Gas Turbine Air Intake - Surface/Depth loading

| | | | | | | | |
|----------------|--|-----|----|-----|-----|-----------------|------|
| HF-B115-07 | 80/20 Blend / Corrugated / Nano | 115 | 27 | 220 | 90 | F7 | 1150 |
| HF-B115-08 | 80/20 Blend / Corrugated / Nano | 115 | 26 | 210 | 95 | F8 | 1150 |
| HF-B115-09 | 80/20 Blend / Corrugated / Nano | 115 | 23 | 185 | 110 | F9 | 1150 |
| HF-B115-10 | 80/20 Blend / Corrugated / Nano | 115 | 16 | 125 | 85 | E10 @0.2-0.3 µm | 1150 |
| HF-B115-11 | 80/20 Blend / Corrugated / Nano | 115 | 11 | 90 | 120 | E11 @0.2-0.3 µm | 1150 |
| HF-SRC130-09 | Bico PET / Corrugated / Nano | 130 | 28 | 225 | 90 | F9 | 750 |
| HF-SRC130-10 | Bico PET / Corrugated / Nano | 130 | 24 | 190 | 55 | E10 @0.2-0.3 µm | 750 |
| HF-SR130-HO-09 | Bico PET / Nano / HO | 130 | 26 | 210 | 95 | F9 | 750 |
| HF-STP70-HO-09 | Bico PET / Multilayer / Nano /Depth/HO | 80 | 31 | 250 | 80 | F9 | 650 |
| HF-STP70-09 | Bico PET / Multilayer / Nano / Depth | 70 | 41 | 333 | 60 | F9 | 650 |
| HF-STP130-09 | Bico PET / Multilayer / Nano / Depth | 135 | 31 | 250 | 80 | F9 – ePM1 85% | 750 |

[See All Product +](#)

The values are for information purposes, the target values are stated in the product TDS

*All data and statements concerning these products may be considered as being indicative of representative properties obtainable. We make no warranty, expressed or implied, concerning actual use or results because of industry specific influenc

Açık Kart Bilgi Teknolojileri Ticaret A.Ş

+90 258 251 5057

www.hifyber.com

sales@hifyber.com

