

Product Code	Description	Weight	Air Permeability	Air Permeability	Initial Pressure Drop	Filtration Class	Roll Length
		gr/m ²	Cfm @125pa	l/m ² .s @200pa	pa	EN779:2012 / EN1822 / ISO 16890 / EN149 / NIOSH 42 CFR 84 / EN14683	mt

Gas Turbine Air Intake - Surface/Depth loading

HF-B115-07	80/20 Blend / Corrugated / Nano	115	27	220	90	F7	1150
HF-B115-08	80/20 Blend / Corrugated / Nano	115	26	210	95	F8	1150
HF-B115-09	80/20 Blend / Corrugated / Nano	115	23	185	110	F9	1150
HF-B115-10	80/20 Blend / Corrugated / Nano	115	16	125	85	E10 @0.2-0.3 µm	1150
HF-B115-11	80/20 Blend / Corrugated / Nano	115	11	90	120	E11 @0.2-0.3 µm	1150
HF-SRC130-09	Bico PET / Corrugated / Nano	130	28	225	90	F9	750
HF-SRC130-10	Bico PET / Corrugated / Nano	130	24	190	55	E10 @0.2-0.3 µm	750
HF-SR130-HO-09	Bico PET / Nano / HO	130	26	210	95	F9	750
HF-STP70-HO-09	Bico PET / Multilayer / Nano /Depth/HO	80	31	250	80	F9	650
HF-STP70-09	Bico PET / Multilayer / Nano / Depth	70	41	333	60	F9	650
HF-STP130-09	Bico PET / Multilayer / Nano / Depth	135	31	250	80	F9 – ePM1 85%	750

See All Product +

The values are for information purposes, the target values are stated in the product TDS

*All data and statements concerning these products may be considered as being indicative of representative properties obtainable. We make no warranty, expressed or implied, concerning actual use or results because of industry specific influenc

Açık Kart Bilgi Teknolojileri Ticaret A.Ş

+90 258 251 5057

www.hifyber.com

sales@hifyber.com

